



STRENGTH YOU  
**FEEL**

**TILE ADHESIVE | EPOXY | GROUT | WATERPROOFING**



**Corporate Office:**

Bilva Trade Hube, 4th Floor, Office No.425,  
Mahendranagar, Jetpar-Pipli Road, Morbi-363642,  
Gujarat,INDIA.

**Call Us: +91 99989 05322 | 12**

info@fixsure.co | www.fixsure.co

Follow Us:    





**FIXSURE**

STRENGTH YOU FEEL

#### What We Do

**Fixsure** is a premium tile adhesive company offering a comprehensive range of high-performance bonding solutions. We are committed to delivering strong, reliable, and long-lasting adhesives suitable for all types of tile installations and block joint applications. Our dedication to quality and innovation has positioned us as one of the leading tile adhesive brands in India.

Our products are specially formulated to withstand challenging conditions such as rain, sunlight, humidity, and pollution—while ensuring superior grip, perfect alignment, and exceptional durability. From residential spaces to large-scale commercial projects, **Fixsure** provides trusted support for every surface—laying the foundation behind every flawless finish.

#### Our Vision & Mission

At **Fixsure**, our mission is to deliver premium tile adhesive solutions that set new benchmarks in strength, reliability, and durability. We are committed to developing and supplying a comprehensive range of products that cater to diverse tiling and block joining needs—ensuring superior bonding performance across all types of surfaces and conditions.

Driven by innovation and guided by industry best practices, we strive to support architects, contractors, and homeowners in achieving perfect finishes that last. Our adhesives are formulated to withstand environmental challenges such as moisture, heat, and pollution—ensuring long-term alignment, grip, and aesthetic integrity.

With a customer-first approach, we focus on delivering consistent quality, technical expertise, and on-time support, making **Fixsure** a trusted partner in building projects of every scale—from modern homes to high-end commercial developments.

**FIXSURE**

STRENGTH YOU FEEL

## Index

- 01 ● **TILES ADHESIVE**
- 02 ● **BLACK JOINTING MORTAR**
- 03 ● **WALL PUTTY**
- 04 ● **TILE GROUT**
- 05 ● **GROUT ADMIXTURE**
- 06 ● **TILES CLEANER**
- 07 ● **TAPO CLEANER**



**FIXSURE**

STRENGTH YOU FEEL

## **TILE & STONE ADHESIVE**

At **Fixsure**, we offer a comprehensive range of tile adhesive products for you to choose from, making us one of the leading tile adhesive manufacturers in India.

Come rain, sunshine, humidity, or pollution, we are the leading tile adhesive manufacturers in India for all the right reasons and will protect your walls and floors from cracking and debonding. Our complete range of products is designed to cater to several different purposes in your homes and offices.



**FIXSURE**

STRENGTH YOU FEEL

## Transform Your Space With FIXSURE



For internal  
& External  
floor & wall



Easy to  
Clean



Non-Cracking



Available  
in different  
Colours



Non-Shrinking



Low VOC







# FS - 01

20 Kg

GREY

## Features

- ✦ Easy To Apply.
- ✦ High Bonding Strength.
- ✦ Very Low Shrinkage Prevents Debonding And Gives Longer Life To Tiles.
- ✦ Premixed Material - Add Only Water.
- ✦ Slip-resistant For Vertical Application
- ✦ Shrinkage Cracks Get Minimized / Eliminated Due To Its Self-curing Properties.

PROPERTIES	RESULTS
Appearance	Free Flowing Powder
Colour	Grey
Pot Life	2.30 Hours
Open Time	40 Min.
Adjustability Time	25 Min.
Trafficable Time, Hrs	16 to 24
Shear Adhesion, Dry Condition (as per annex B)	1.05 - 1.20
Tensile Adhesion, Dry Condition (as per annex A)	0.6 - 0.7
EN 12004 Standards	C1T



## Product Description

**FS-01** is First grade of **FIXSURE** tiles adhesive. According to the ISI, the product meets CITE category parameters. The **FIXSURE** is recommended tiles adhesive for wall tiles and flooring tiles, marble and stone. We can use **FIXSURE** Tiles Adhesive for below purposes.

FS-01 **FIXSURE** Tile Adhesive complies to requirements of IS 15477 : 2019 - Type 1 'T' "Specification for Adhesives for use with Ceramic Tiles and Mosaics.

## Area of Applications

Cementitious screed and plasters in internal areas.

**Floor:-** Ceramic Wall & Porcelain Tiles 200X200, 300x300, 300x600, 600x600 mm

**Pack Size :** 20 kg

**Colour :** Grey

**Coverage :** For a 3 mm bed thickness & after using of notch trowel, the coverage will be approximately 4-4.5 kg/ sq. mtr.

**Note :** The coverage will vary depending on trowel notch size, type, size of tile and substrate smoothness and evenness.

**Shelf Life :** 12 Month form the month & year of manufacturing when sealed packed & stored in proper (dry place) condition.



# FIXSURE

STRENGTH YOU FEEL

## FS - 02

20 Kg

GREY

WHITE

### Features

- ✦ Easy To Apply.
- ✦ Premixed Material - Add Only Water
- ✦ Highly Polymer Modified - Provides High Adhesion, Allows To Bond With Variety Of Substrates, For Fixing A Variety Of Tiles And Stones
- ✦ Sag Resistant Formula : Provides Hassle-free Application On Vertical Walls
- ✦ Water Resistant - Suitable For Wet Areas & Commercial Floor Too
- ✦ Sustains Heat Ageing - Making It Ideal For High Temperature Locations And For Hot Temperature Applications, Like Jacuzzi, Sauna, Etc.

PROPERTIES	RESULTS
Appearance	Free Flowing Powder
Colour	Grey/White
Pot Life	2.30 Hours
Open Time	40 Min.
Adjustability Time	25 Min.
Trafficable Time, Hrs	16 to 24
Shear Adhesion, Dry Condition (as per annex B)	1.25-1.40 N/MM2
Tensile Adhesion, Dry Condition (as per annex A)	1.05-1.20 N/MM2
EN 12004 Standards	C2T



# FIXSURE

STRENGTH YOU FEEL

### Product Description

**FS-02** Adhesive is a polymer modified, thin-set tile adhesive for fixing ceramic, semi-vitreous tile, vitrified tiles & natural stones of regular size. It is suitable for both vertical and horizontal surfaces, over the cementitious substrate for indoor application, in dry as well as wet areas.

**FS-02** Adhesive complies to Type 2 'T' as per "IS 15477:2019 - adhesives for use with Ceramic Tiles and Mosaics - specification

Also, **FIXSURE FS-02** conforms to class C2 T as per ISO 13007 - a cementitious (C) Normal Adhesive (1) slip resistant (T) Extended Open Time.

### Area of Applications

All types of ceramic tile, terracotta, vitrified tiles, large format tiles, precast terrazzo, natural stones, low thickness slabs

Cement-based screeds / bed, gypsum & cement based plasters / renders, concrete surfaces & bricks, existing tiles & stones, waterproofing products, other cement-based surface

**Wall:-** Ceramic Wall & Porcelain Tiles ( 300x600, 600X600, 600X1200 ,1000x1000mm )

**Floor:-** Ceramic Wall & Porcelain Tiles (300x600, 600x600, 800X800, 600X1200, 800X1600 mm)

**Pack Size:- 20 KG**

**Colour :** Grey & White

**Coverage:-** For a 3 mm bed thickness & after using of notch trowel, the coverage will be approximately 4-4.5 kg/ sq. mtr.

**Note :** The coverage will vary depending on trowel notch size, type, size of tile and substrate smoothness and evenness.

**Shelf Life :-** 12 Month form the month & year of manufacturing when sealed packed & stored in proper (dry place) condition.



# FS - 03

20 Kg

GREY

WHITE

## Features

- ✦ Easy To Apply.
- ✦ Premixed Material - Add Only Water
- ✦ Highly Polymer Modified - Provides High Adhesion, Allows To Bond With Variety Of Substrates, For Fixing A Variety Of Tiles And Stones
- ✦ Sag Resistant Formula : Provides Hassle-free Application On Vertical Walls
- ✦ Flexible Adhesive - Allows To Sustain Minor Vibration In Substrate.
- ✦ Long Open Time - Suitable For Large Format & External Condition
- ✦ Water & Shock Resistant - Suitable For Wet Areas & Commercial Floor Too.
- ✦ Sustains Heat Ageing - Making It Ideal For High Temperature Locations And For Hot Temperature Applications, Like Jacuzzi, Sauna, Etc.
- ✦ Low Voc - For Healthy Living.

PROPERTIES	RESULTS
Appearance	Free Flowing Powder
Colour	Grey/White
Pot Life	2.30 Hours
Open Time	35 Min.
Adjustability Time	20 Min.
Trafficable Time, Hrs	16 to 24
Shear Adhesion, Dry Condition (as per annex B)	1.60-1.70 N/MM2
Tensile Adhesion, Dry Condition (as per annex A)	1.60-1.65 N/MM2
EN 12004 Standards	C2TE S1



## Product Description

**FS-03 FIXSURE** Adhesive is a highly polymer modified, thin-set tile adhesive for fixing for all type of tiles, mosaics and natural stones, on a variety of surfaces, for both vertical and horizontal application, in dry as well as wet areas for indoor as well as outdoor application. It can be used to fix regular size tile in commercial area as it accommodates shocks due to heavy traffic.

**FS-03** Adhesive complies to Type 3 ‘T’ as per “IS 15477:2019 - adhesives for use with ceramic, mosaic and Stone tiles – Specification

Also, **FIXSURE FS-03** conforms to class C2 TE as per ISO 13007 - a cementitious (C) Normal Adhesive (1) slip resistant (T) Extended Open Time (E) tile adhesive.

## Area of Applications

All types of ceramic tile, terracotta, pavers, vitrified tiles, glass mosaic tiles, large format tiles, precast terrazzo, marble & natural stones, low thickness slabs.

Cement-based screeds/ bed, gypsum & cement based plasters/ renders, concrete surfaces & bricks, existing tiles & stones, other cement-based surface, waterproofing products, drywall like cement /bison/ gypsum boards\* .

**Wall:-** Ceramic Wall & Porcelain Tiles (300x300, 300x600, 600X600, 600X1200, 800x1600, 1200x1200, 1200x1800 mm )

**Floor:-** Ceramic Wall & Porcelain Tiles ( 300x300, 300x600, 600x600, 800X800, 600X1200, 800X1600, 1200x1800, 1200X2400 mm )

**Pack Size:- 20 KG                      Colour :** Grey & White

**Coverage:-** For a 3 mm bed thickness & after using of notch trowel, the coverage will be approximately 4-4.5 kg/ sq. mtr.

**Note :** The coverage will vary depending on trowel notch size, type, size of tile and substrate smoothness and evenness.

**Shelf Life :-** 12 Month form the month & year of manufacturing when sealed packed & stored in proper (dry place) condition.





# FS - 04

20 Kg

GREY

WHITE

## Features

- ✦ Easy To Apply.
- ✦ Premixed Material - Add Only Water
- ✦ Highly Polymer Modified - Provides High Adhesion, Allows To Bond With Variety Of Substrates, For Fixing A Variety Of Tiles And Stones
- ✦ Sag Resistant Formula : Provides Hassle-free Application On Vertical Walls
- ✦ Flexible Adhesive - Allows To Sustain Minor Vibration In Substrate.
- ✦ Long Open Time - Suitable For Large Format & External Condition
- ✦ Water & Shock Resistant - Suitable For Wet Areas & Commercial Floor Too.
- ✦ Sustains Heat Ageing - Making It Ideal For High Temperature Locations And For Hot Temperature Applications, Like Jacuzzi, Sauna, Etc.
- ✦ Low Voc - For Healthy Living

PROPERTIES	RESULTS
Appearance	Free Flowing Powder
Colour	Grey/White
Pot Life	2.30 Hours
Open Time	35 Min.
Adjustability Time	20 Min.
Trafficable Time, Hrs	16 to 24
Shear Adhesion, Dry Condition (as per annex B)	1.70-1.80 N/MM2
Tensile Adhesion, Dry Condition (as per annex A)	1.80-1.90 N/MM2
EN 12004 Standards	C2TE S1



## Product Description

**FS-04 FIXSURE** Adhesive is a high polymer modified & highly flexible adhesive with enhanced properties of slip resistant, extended open time & excellent bond strength which is necessary for fixing large format tiles/ natural stones & slim tiles on vertical & horizontal surface for indoor as well as outdoor application especially in external conditions & on substrates subject to deformations/ vibrations.

**FS-04** a Adhesive complies to Type 4 ‘T S1’ as per “IS 15477: 2019 - Adhesives for use with ceramic, mosaic and stone tiles – Specification

Also, **FIXSURE FS-04** Adhesive conforms to class C2TES1 as per ISO 13007 - a cementitious (C) improved performance (2) slip resistant (T) deformable (S1) with extended open time (E) tile adhesive

## Area of Applications

All types of ceramic tile, terracotta, pavers, brick, vitrified tiles, glass mosaic tiles, large format tiles, precast terrazzo, marble & natural stones, low thickness slabs.

Cement-based screeds/ bed, gypsum & cement based asters/ renders, concrete surfaces & bricks, existing tiles & stones, other cement-based surface, waterproofing products, drywall like cement /bison/ gypsum/ fibre boards etc\* , Thermal insulation panel.

**Wall:-** Ceramic Wall & Porcelain Tiles ( 300x300, 300x600, 600X600, 600X1200, 800x1600, 800X2400, 1200X2400, 1600X3200 mm )

**Floor:-** Ceramic Wall & Porcelain Tiles ( 300x300, 300x600, 600x600, 800X800, 600X1200, 800X1600, 1200x1800, 1200X2400, 1200X3200, 1600X3200 mm )

**Pack Size:- 20 KG**

**Coverage:-** For a 3 mm bed thickness & after using of notch trowel, the coverage will be approximately 4-4.5 kg/ sq. mtr.

**Note :** The coverage will vary depending on trowel notch size, type, size of tile and substrate smoothness and evenness.

**Shelf Life :-** 12 Month form the month & year of manufacturing when sealed packed & stored in proper (dry place) condition.



# BLOCK JOINT MORTAR

20 Kg  
GREY

## Features

- ✦ High Strength
- ✦ No Curing Required After Block Work Is Done.
- ✦ Flexible, Shock & Impact Resistant
- ✦ Improved Adhesion Between Two Blocks
- ✦ Improved Bond Strength, Compressive & Tensile Strength
- ✦ Thin Jointing With High Adhesion To Contribute To Load Bearing Capacity Of Masonry
- ✦ Easy To Use
- ✦ Long Working Time
- ✦ Fast & Economical

PROPERTIES	RESULTS
Appearance	Powder Grey
Water Demand	10 to 30%
Compressive Strength	>15 N/mm2 @28 Days
Tensile Strength	>0.8 N/mm2 @28 Days
Hard Dry	24 Hour
Pot Life	Approx 2 Hour



## Product Description

Block Joint Mortar **FIXSURE** Block Joint Mortar is a factory prepared blend of carefully selected raw materials, Portland cement and graded aggregates and polymers. Designed for use with water to produce high strength thixotropic mortar, for laying Aerated Light weight concrete, Fly ash bricks, cement hollow blocks, Cellular concrete blocks or smoothing over the block work surface in layers of up to 12mm thickness, that meet and exceed the requirements of National and International Standards.

Area Of Usage It can be used on all types of exterior cement plasters/interior walls, asbestos sheets, concrete etc

## Area of Applications

For interior and exterior use for preparing thin bed adhesive for AAC, ALC and cellular concrete blocks

Actual coverage may vary from the quoted figures due to factors such as method of application, environmental conditions and surface texture.

**Pack Size:- 20 KG**

**Shelf Life :-** 1 year from date of manufacture in original tightly sealed sacks away from direct sunlight and excessive heat..



**FIXSURE**

STRENGTH YOU FEEL

# WALL PUTTY

**40 Kg****WHITE**

## Features

- ✦ Provides Smooth And Uniform Finish To Rough Plasters
- ✦ Good Workability
- ✦ Does Not Require Curing With Water
- ✦ Good Water Resistance
- ✦ Good Tensile Adhesion Strength, Compressive Strength And Flexural Strength
- ✦ Controlled Water Vapour Permeability
- ✦ Excellent Abrasion Resistance
- ✦ Resists Growth Of Algae And Fungi On Wall
- ✦ Good Intercoat Adhesion To Emulsion Paints

**FIXSURE**

STRENGTH YOU FEEL

## Product Description

Wall Putty **FIXSURE** Wall Putty is a white cement based product with redispersible polymer and functional additives for application on interior and exterior rough plasters to give a smooth finish.

Area Of Usage It can be used on all types of exterior cement plasters/interior walls, asbestos sheets, concrete etc

## Area of Applications

It can be used on all types of exterior cement plasters/interior walls, asbestos sheets, concrete, etc

On rough masonry surface by putty knife 2 COATS 10 - 15 sq.ft/kg for upto 1.5 mm thickness in 2 coats

**Pack Size:- 40 KG**

**Shelf Life :-** 12 Month form the month & year of manufacturing when sealed packed & stored in proper (dry place) condition.

**FIXSURE**

STRENGTH YOU FEEL

# TILE GROUT

1 Kg

## Features

- ✦ Easy To Use & Clean - Just Mix With Water, Ready To Use.
- ✦ Polymer Modified - Crack Free, Minimum Shrinkage & Water Resistance
- ✦ Suitable For Varied Tile And Stones - All Ceramic, Vitrified Tiles, Granites Etc.
- ✦ Available In Range Of Attractive Colors
- ✦ Best Results Obtained When Used In Conjunction With Fixsure Grout Admixture
- ✦ Low Voc - For Healthy Living.

## TILE GROUT COLOUR

501 White	502 Ivory
503 Steel Grey	504 Grey
505 Dark Grey	506 Pink
507 Brown	508 Black
509 Golden Yellow	510 Chocolate Brown
511 Sky Blue	



**FIXSURE**

STRENGTH YOU FEEL

## Product Description

**FIXSURE** Tile Grout is a polymer modified, cement-based tile joint filler used for filling the joints/ gap between the tiles. It effectively fills the gaps and gives water resistant, non-dusting tile joints. It is designed for grouting glazed, ceramic, porcelain, vitrified & fully vitrified tiles & natural stones.

**FIXSURE** Tile Grout complies to CG2W requirements as per “BS EN 13888:2009 - Requirements, evaluation of conformity, classification and designation gouts for tiles and ISO 13007- Part 3: Terms, definitions and specifications for grouts”.

## Area of Applications

All types of ceramic tile, glazed tiles, porcelain tiles, vitrified & fully vitrified tiles, natural stones\*, glass mosaic tiles.

**Note :** For highly absorbent natural stones/ marbles which may form a wet or colored patch when tile grout is applied, do sample test to check for possible staining. It is recommended to use suitable FIXSURE Impregnating sealer on all sides & mask the tiles before grouting.

Best results obtained when used in conjunction with FIXSURE Grout Admixture. The addition of FIXSURE Grout Admixture to cement based grouts will enhance adhesion to tile/stone edges, reduce water permeability and imparts flexibility which would be needed for wider gap up to 6mm, wet areas, commercial applications & external areas



**FIXSURE**

STRENGTH YOU FEEL

## EPOXY GROUT

1 Kg

5 Kg

### Features

- ✦ Stainless - Will Not Be Stained By Most Foods, Beverages And Cleaning Agents.
- ✦ Easy Maintenance - Smooth Texture, Easier To Clean.
- ✦ Provides Excellent Chemical Resistant To Many Acids, Alkalis And Corrosives.
- ✦ Provides Hygienic, Hard Wearing And Abrasion Resistant Surface
- ✦ Waterproof Property
- ✦ Durable - Will Not Peel, Crack Or Powdering.
- ✦ Excellent Mechanical Property & Highly Resistant To Heavy Traffic.
- ✦ Easy To Use - No Noxious Odor, Nonflammable, Water Cleanable, Easy To Clean.
- ✦ Stable And Uniform Coloring For All Types Of Tiles



**FIXSURE**

STRENGTH YOU FEEL

### Product Description

**FIXSURE** Epoxy Grout is a stainless, chemical resistant, hard wearing & impervious epoxy - based tile joint filler which has high degree of resistance to abrasion, impact & shocks. It is designed for grouting gap between glazed, ceramic, porcelain, vitrified & fully vitrified tiles, natural stones & Glass mosaics. Gruton Epoxy Grout can also be used as a high-performance epoxy adhesive for fixing tiles & Stone.

### Area of Applications

All types of ceramic tile, glazed tiles, porcelain tiles, vitrified & fully vitrified tiles, natural stones\*, large format tiles, glass mosaic tiles, composites & engineered stone

Floor & walls of internal & external area\*, dry as well as wet area, water submerged area, food, pharma & hygiene required areas, area containing aggressive chemicals\*, heavy traffic/ movement areas, domestic applications, commercial applications, wider tile joints

**Note :** For highly absorbent natural stones/ marbles which may form a wet or colored patch when tile grout is applied, do sample test to check for possible staining. It is recommended to use suitable Fixsure Impregnating sealer on all sides & mask the tiles before grouting.

For external application, please contact FIXSURE personnel for technical assistance.

See chemical resistance table for chemical areas

## Coverage

Consumption table dependent on the size of the tiles and width of the joints (kg/m²)

Tile Dimension (mm)			Joint / Grouting Width (mm)							
Length	Width	Thickness	2	3	4	5	6	8	10	12
25	25	6	1.68	2.52	3.36	4.20	5.04	6.72	8.40	10.1
25	50	6	1.26	1.89	2.52	3.15	3.78	5.04	6.30	7.56
50	50	6	0.84	1.26	1.68	2.10	2.52	3.36	4.20	5.04
100	100	6	0.42	0.63	0.84	1.05	1.26	1.68	2.10	2.52
100	100	10	0.70	1.05	1.40	1.75	2.10	2.80	3.50	4.2
300	200	6	0.18	0.26	0.35	0.44	0.53	0.70	0.88	1.05
300	300	6	0.14	0.21	0.28	0.35	0.42	0.56	0.70	0.84
450	300	6	0.12	0.18	0.23	0.29	0.35	0.47	0.58	0.7
600	300	6	0.11	0.16	0.21	0.26	0.32	0.42	0.53	0.63
600	600	8	0.09	0.14	0.19	0.23	0.28	0.37	0.47	0.56
800	800	8	0.07	0.11	0.14	0.18	0.21	0.28	0.35	0.42
1000	1000	10	0.07	0.11	0.14	0.18	0.21	0.28	0.35	0.42
1200	600	10	0.09	0.13	0.18	0.22	0.26	0.35	0.44	0.52
1200	800	10	0.07	0.11	0.15	0.18	0.22	0.29	0.36	0.44
1200	1200	12	0.07	0.11	0.14	0.18	0.21	0.28	0.35	0.42
1600	800	12	0.08	0.12	0.16	0.20	0.24	0.32	0.39	0.47
1800	1200	12	0.06	0.09	0.12	0.15	0.18	0.23	0.29	0.35

\* Coverage mentioned in table is indicative only and can vary as per the tile size, thickness, joint width & wastage during application.

## Features & Advantages

- ✦Stainless – Will not be stained by most foods, beverages and cleaning agents
- ✦Easy Maintenance – Smooth texture, easier to clean.
- ✦Provides excellent chemical resistant to many acids, alkalis and corrosives.
- ✦Provides hygienic, hard wearing and abrasion resistant surface.
- ✦Waterproof property
- ✦Durable – Will not peel, crack or powdering
- ✦Excellent mechanical property & highly resistant to heavy traffic.
- ✦Easy to Use – No noxious odor, nonflammable, water cleanable, easy to clean.
- ✦Stable and uniform coloring for all types of tiles.





✦ ALL COLOURS ARE AVAILABLE IN SILVER,  
GOLDEN, COPPER GLITTER SPARKLE\*  
Actual shade & texture will depend  
on jobsite condition

2 & 3-PART Color Chart

	101 White
	102 Ivory
	103 Steel Grey
	104 Grey
	105 Dark Grey
	106 Pink
	107 Brown
	108 Sky Blue
	109 Golden Yellow
	110 Burgundy
	111 Red
	112 Chocolate Brown
	113 Wood Brown
	114 Antique Green
	115 Dark Blue
	116 Coffee Brown
	117 Red Brown
	118 Black
	119 Terra Cotta
	120 Mid Orange
	121 Dark Brown



Sparkle Color Chart

SILVER COLOR
GOLDEN COLOR
COPPER COLOR



**FIXSURE**

STRENGTH YOU FEEL

## ***GROUT ADMIXTURE***

**500 ml.****200 ml.**

### **Features**

- ✦ Easy To Use & Clean - Just Mix With Gruton Tile Grout On Site, Ready To Use
- ✦ Polymer Emulsion - Impart Flexibility, Water & Stain Resistant, Abrasion Resistant.
- ✦ Suitable For Varied Tile And Stones - Ceramic, Vitrified, Marbles, Granites Etc.
- ✦ Crack Free And Less Of Shrinkage Reduces The Chances Of Water Seepage.
- ✦ Durable - Enhances Compressive & Flexural Strength And Shock Resistance.

**FIXSURE**

STRENGTH YOU FEEL

### **Product Description**

FIXSURE Grout Admixture is a white, polymer emulsion to be added in FIXSURE cementitious tile grout to enhance the performance properties and durability of the tile grout. Addition of FIXSURE Grout Admixture with FIXSURE Tile Grout helps to impart more flexibility, strength, water & stain resistance, abrasion resistance and to fill wider joints between tile and stone

### **Area of Applications**

All types of ceramic tile, glazed & porcelain tiles, vitrified & fully vitrified tiles, natural stones\* , large format tiles, glass mosaic tiles.

Floor and walls, internal & external area\* , domestic applications, commercial applications\* , wider tile joints up to 6 mm.



**FIXSURE**

STRENGTH YOU FEEL

## ***TILE CLEANER***

1 Ltr.

250 ml.

### **Features**

- ✦ Easy To Use - Just Mix With Water & Clean The Surface.
- ✦ Removes Difficult Stains Easily - Fast & Effective.
- ✦ Degreases The Tile Surface Easily For Soaps, Scum, Efflorescence, Mineral Deposit
- ✦ Cleans All Types Of Tile Like Ceramic, Porcelain & Vitrified Tile And Grout.
- ✦ Protects The Color & Shine Of Tile
- ✦ Does Not Damage Joints Between Ceramic Tiles, Even Those Grouted With Colored Products.
- ✦ Not Harmful Like Acid.

### **Product Description**

FIXSURE Tile Cleaner is a high quality rapid active cleaner and degreasing solution for use on tiles, bathtubs, wash basin, privy basin and concrete etc. It is used to clean whitish spot/ layer as normally observed in the bathroom under plastic/ metal buckets (normal detergent is not helpful) with ease

It is also used as rapid removal of white yellowish spot/layer along with water stains over tiles, cement stains, grime, oil, paint stains, grease, moss and wax from concrete, asbestos, terrazzo and ceramics.

### **Area of Applications**

Stain cleaning for ceramic tile, glazed tiles, porcelain tiles, vitrified tiles, glass mosaic tiles & sanitaryware. Cleaning moss and wax from concrete, asbestos, terrazzo and ceramics. Surface before & after application of epoxy products. Natural stones\*

Cleaning floor and wall tiling in kitchen, bathrooms, toilets, garages, factories, general building sites & residential tiling. Internal & external tiling area. Domestic & commercial tiling area. Routing tile cleaning with mop in bathroom & other tiling area.

**Pack Size:- 250ml & 1ltr**

**Note :-** FIXSURE Tile Cleaner before using for cleaning of coloured concrete, granite, marble stone flooring with corner test because it may etch the surface. (If stone shows discoloration up to 24 hrs. after application, do not use product).



**FIXSURE**

STRENGTH YOU FEEL

## ***TAPO CLEANER***

1 Ltr.

250 ml.

### **Features**

- ✦ Easy To Use - Just Spray & Clean By Brush / Cotton
- ✦ Removes Difficult Stains Easily - Fast & Effective
- ✦ Degreases The Tile Surface Easily For Soaps, Scum, Efflorescence, Mineral Deposit. Protects The Color & Shine
- ✦ Not Harmful Like Acid.

### **Product Description**

FIXSURE Tapo Cleaner is a high quality rapid active cleaner and degreasing solution for use on bathroom fittings, ss kitchen sinks, etc.

### **Area of Applications**

FIXSURE Tapo Cleaner For Bathroom Faucets & Accessories, Taps, Showers, Etc.

Home Care, Hospitals, Hotels & Restaurants, Resorts, Corporate Offices, Shopping Malls, Machineries & Industries.

**Pack Size:- 250ml & 1ltr**





### Tile Spacers

Our high-quality tile spacers are meticulously designed to maintain consistent spacing between tiles, ensuring precise alignment throughout your tiling project. Available in a range of sizes from 2 mm to 10 mm, these spacers guarantee a professional finish when used in conjunction with suitable grout.

- Prevents Tile Shifting
- Strong & Durable Material
- Precise Tile Alignment

### Tile Wedges

FIXSURE Tile Wedges are the perfect solution for achieving precise tile leveling and alignment during installation. Designed to work with tile clips, they help maintain even spacing and prevent tile movement, ensuring a flawless finish. Made from durable, high-quality material, these wedges provide excellent grip and stability, making the tiling process faster and more efficient. Ideal for ceramic, vitrified, and large-format tiles, FIXSURE Tile Wedges guarantee a professional look with minimal effort.

- Hassle-Free Removal
- Prevents Uneven Tiles
- Accurate Tile Leveling



### Tile Clips

FIXSURE Tile Clips are designed to ensure perfectly leveled and aligned tiles, preventing lippage and uneven surfaces. Ideal for both wall and floor installations, these clips provide stability and precision during the tiling process. Made from durable, high-quality material, they hold tiles securely in place, making installation faster and more efficient. Suitable for ceramic, vitrified, and large-format tiles, FIXSURE Tile Clips guarantee a seamless finish with minimal effort, enhancing the overall aesthetics and durability of tiled surfaces.

- Faster Installation
- Prevents Tile Shifting
- Strong & Durable Material



### Notch Trowel

FIXSURE Notch Trowel is an application tool that is used to spread tile and stone adhesives at the time of tile fixing. This application tool is manufactured with top- quality material and advanced techniques to make it highly useful in evenly spreading tile adhesives during tile installation. This is why FIXSURE's notch trowel, made of steel

Surface on which it is used: Use it on all types of ceramic tiles: glazed tiles, porcelain tiles, vitrified tiles, fully vitrified tiles, natural stones\*, large format tiles, glass mosaic tiles, composite stones, and engineered stones

Area of application: It can be used on floors and walls in internal and external areas, in domestic as well as commercial applications

- **Easy to apply:** A notched trowel takes out a thin set of tile adhesive to spread it over the substrate. The trowel has defined notches on the sides that help create an even base for the tile to sit perfectly on the substrate.
- **Proper levelling:** The notches that are either square, V-shaped, or U-shaped create a level surface so that tiles are properly aligned. The application tool ensures that extra adhesive does not sit on the surface, which gives professional-looking tiled walls and floors.
- **Full coverage with better bonding:** coverage is very important if you want to achieve better bonding between the substrate and tiles. A notched trowel creates an even surface where the tiles are placed to form a strong bond with the substrate.
- **Less time consumption and faster work:** Professionals use a notch trowel tool to speed up the tile fixing process. This tool helps in getting a professional tile application in less time and eases the application work.

### TILE & GLASS SUCTION CUP

FIXSURE tile suction cup is a versatile tool designed for handling and manipulating tiles, glass, and other smooth surfaces. Here's a description of a typical tile suction cup.

Typically made from durable, high-quality materials like rubber or silicone for the suction cup itself and a sturdy plastic or metal for the handle.

Some advanced models might include additional features like multiple suction cups for increased stability, adjustable handles, or ergonomic designs for better grip and control.

- **Ideal for tile installation, removal, or repositioning, as well as for handling glass, mirrors, and other smooth materials. The suction cup minimizes the risk of damage and makes it easier to maneuver large or heavy items**

